

Interim Report
I-A2049-27

Technical Report

DETERMINATION OF GAS BEARING STABILITY
BY RESPONSE TO A STEP-JUMP

by

H. G. Elrod, Jr.
J. T. McCabe
T. Y. Chu

Prepared under

Contract Nonr-2342 (00)
Task NR 062-316

Supported Jointly by

DEPARTMENT OF DEFENSE
ATOMIC ENERGY COMMISSION
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Administered by

OFFICE OF NAVAL RESEARCH
Department of the Navy

Reproduction in Whole or in Part is Permitted for
any Purpose of the U. S. Government



THE FRANKLIN INSTITUTE RESEARCH LABORATORIES

BENJAMIN FRANKLIN PARKWAY AT 20TH STREET, PHILA. 3, PA.

N 66 34682

ABSTRACT

The stability of a gas bearing is treated by a new procedure in which the bearing film is characterized by its responses to step-jump displacements. Duhamel's theorem is invoked to generalize these step responses in a system of dynamical equations. Stability is determined by calculation of a "growth factor" for each degree of freedom.

Author

NOMENCLATURE

- A_n = nth LaGuerre coefficient (equation 8)
 B_j = jth LaGuerre coefficient (equation 10)
 C = Ground-in clearance
 F_{ij} = the force in the "j" direction due to a displacement in the "i" direction
 δF_{ij} = the difference in F_{ij} between time t and equilibrium at time zero (equation 4)
 $H(t-\tau)$ = the response function observed at time t produced by stimulus at time τ (equation 4)
 I_T, I_p = shaft transverse and polar moments of inertia
 L = length of bearing
 L_1, L_2 = distances from shaft mass center to bearings one, two
 $L_n(x)$ = nth LaGuerre polynomial (equation 6)
 M = shaft mass
 p_a = ambient pressure
 R = shaft radius
 $r(t)$ = a response function (equation 3)
 $s(t)$ = a stimulus (equation 3)
 t = time variable
 W_i = Gauss integration weighting factors
 $\delta x, \delta y$ = small displacements in x and y directions
 α = attenuation constant
 α_1, α_2 = shaft angular coordinates
 β = growth factor (equation 14)

NOMENCLATURE (Cont.)

γ = growth frequency (equation 15)

ϵ = eccentricity ratio

$$\Lambda = \frac{6\mu\Omega}{p_a} \left(\frac{R}{C}\right)^2$$

μ = viscosity

τ = dummy variable

Ω = shaft angular speed

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT.	i
NOMENCLATURE.	ii
1. INTRODUCTION.	1
2. TECHNICAL DISCUSSION.	3
2.1 Response to Step-Jump.	3
2.2 Gas-Bearing Response Functions	4
2.3 Stability Characteristics of the Infinitely Long Self- Acting Gas Journal Bearing	9
2.4 Stability Characteristics of a Two-Bearing System.	16
3. CONCLUSIONS	25
4. RECOMMENDATIONS	26
REFERENCES.	27
APPENDIX A.	A1

LIST OF FIGURES

<u>Fig. No.</u>		<u>Page</u>
2-1	Approximation of "Forcing Function" by Successive Step-Jumps.	4
2-2	Infinitely-Long Gas-Lubricated Journal Bearing	5
2-3	Force Response to Step-Jump for an Infinitely Long Journal Bearing - H_{xx} and H_{yy} vs. Time	6
2-4	Force Response to Step-Jump for an Infinitely Long Journal Bearing - H_{xy} and H_{yx} vs. Time	7
2-5	Response to Small Perturbation About an Equilibrium Position for Infinitely Long Journal Bearing Orbit-Plot of Shaft Mass Center Coordinates	10
2-6	Response to Small Perturbation About an Equilibrium Position for Infinitely Long Journal Bearing Orbit-Plot of Shaft Mass Center Coordinates	11
2-7	Response to Small Perturbation About an Equilibrium Position for Infinitely Long Journal Bearing Orbit-Plot of Shaft Mass Center Coordinates	12
2-8	Single Bearing - Translational Stability	14
2-9	The Critical Translation Stability Ratio, Single Bearing, $L/D \rightarrow \infty$ (After H. Marsh)	15
2-10	The Translational Critical Frequency Ratio, Single Bearing, $L/D \rightarrow \infty$ (After H. Marsh).	15
2-11	Journal Coordinate System.	17
2-12	Translational Motion of Two Bearing System-Shaft Mass Center Coordinates vs. Time.	19
2-13	Conical Motion of Two Bearing System Shaft-Angular Coordinates vs. Time	20
2-14	Translational Motion of Two Bearing System-Shaft Mass Center Coordinates vs. Time.	21



LIST OF FIGURES (Concl.)

<u>Fig. No.</u>		<u>Page</u>
2-15	Conical Motion of Two Bearing System Shaft-Angular Coordinates vs. Time.	22
2-16	Conical Motion of Two Bearing System-Angular Coordinates of Shaft - α_1 vs. α_2	23
2-17	Two Bearing System - Critical Bearing Separation.	24

1. INTRODUCTION

Recent interest in gas hybrid journal bearings has promoted a closer look at the stability of rotor-bearing systems and, in particular, at the methods by which stability might be predicted. In general, two different methods have been used to handle the mathematical stability problem. The first method treats small perturbations from a hypothesized steady-state mode of operation and determines whether these perturbations grow or diminish. The Routh-Hurwitz criterion is used in this connection. The second method consists of direct digital computation of all dynamical and fluid film equations and is known as the "orbit" method. It can handle linear, as well as non-linear, aspects of the problem. Both procedures have been employed extensively in earlier gas-bearing stability work at The Franklin Institute ^{(1,2,3)*} and elsewhere.

The foregoing methods of stability analysis have their advantages and disadvantages. The advantage of the perturbation method is principally that of any linearized analysis; namely, that superposition is possible and results are easily generalized. It has the disadvantage that unusual geometries are not easily accommodated and that in multi-degree-of-freedom systems the characteristic equation is exceedingly complicated. The second method has great flexibility, and can incorporate grooves and other aspects of bearing design quite readily. It gives shaft and film behavior in great detail. It is excellent for delineating the performance of a particular design, but the lack of generality of its solution makes parametric investigations expensive. Its principal disadvantage is its consumption of considerable computer time.

A new procedure for stability analysis is presented here which utilizes the strong points of both the orbit and the linearized approaches. The procedure obviates the necessity for a solution of a large character-

* Number in parenthesis refer to references.

istic equation on the one hand, while avoiding repetitious calculations of fluid-film pressure distributions on the other. Briefly, the method consists of using an orbit program to give the responses to step-jump displacements in each degree of freedom of a system. By means of Duhammel's theorem⁽⁴⁾ these step responses can be used in a system of dynamical equations. A possibility then exists of running linearized orbit programs without the necessity of detailed fluid-film calculations for every case studies. The computing time of the original orbit program is thereby greatly lessened.

2. TECHNICAL DISCUSSION

2.1 Response To Step-Jump

In a linear system, superposition of forcing functions leads to superposition of responses. If the system stimulation is sinusoidal in character, the methods of Fourier synthesis can be used to predict responses to generalized forcing functions. The same sort of generalization is also possible if the response to step-jump stimulus is known, and because this type of response is more readily obtained from an orbit program, the analysis here will be based upon it.

Generalization of the response to step-jump, can be accomplished by means of Duhamel's Theorem. A brief heuristic derivation is as follows: Suppose that $r(t)$, a response, is linearly related to $s(t)$, a stimulus. Let $H(t-\tau)$ denote the r -function observed by time, t , as produced by unit increase of the s -function at time, τ . Then we can consider the more general response occasioned by a more general stimulus to be obtained by superimposed step-jumps as shown in Figure 2-1. The jagged contour can be made to approximate the smooth curve with arbitrarily high precision by reduction of $\Delta\tau$. Clearly,

$$\begin{aligned} r(t) &= s(0) H(t) + \sum_n (\Delta s)_n H(t - n\Delta\tau), \\ &= s(0) H(t) + \sum_n \left(\frac{\Delta s}{\Delta\tau}\right)_n H(t - n\Delta\tau) \Delta\tau. \end{aligned} \quad [1]$$

With $n\Delta\tau = \tau$, and $n \rightarrow \infty$, $\Delta\tau \rightarrow 0$, this equation becomes

$$r(t) = s(0) H(t) + \int_0^t \dot{s}(\tau) H(t-\tau) d\tau. \quad [2]$$




FIG.2-1 APPROXIMATION OF "FORCING FUNCTION" BY SUCCESSIVE STEP-JUMPS


Alternatively, integration by parts gives:

$$r(t) = H(o) s(t) + \int_0^t s(\tau) \dot{H}(t-\tau) d\tau. \quad [3]$$

This second form is found more useful in present applications.

2.2 Gas-Bearing Response Functions

To illustrate the character of the response to step-jump in a typical gas-bearing application, let us consider the forces on an infinitely-long gas-lubricated journal bearing, as shown in Figure 2.2. Corresponding to some vertical loading, the shaft center will, if stable, assume some equilibrium position (x_o, y_o) . In this case the integrated fluid film forces become: $F_x = 0$, $F_y = \text{load}$. Now if the shaft is suddenly given a small x-wise displacement, δx , and held there, both F_x and F_y will be affected. There will be transient force responses to the step-jump in "x" and new steady-state forces will asymptotically be



**FIG. 2-2. INFINITELY-LONG GAS-LUBRICATED
JOURNAL BEARING**

achieved. Similar results can be found for any small y -displacement, δy . Typically, the results due to unit δx_i at $t = 0$ can be expressed as:

$$\delta F_{ij} = F_j(t) - F_j(x_o, y_o); H_{ij} = C \delta F_{ij} / p_a R L. \quad [4]$$

Orbit programs are well suited to provide responses for the kind of displacement just hypothesized. Figures 2-3 and 2-4 give computer results for an infinite journal bearing operating with $\epsilon = 0.6$, $\Lambda = 1.46$. It should be noted that the \bar{n}_{ij} curves give total dimensionless shaft forces -- not fluid film details -- and that these same curves always apply for small deviations from the specified operating condition, regardless of the rest of the shaft dynamics. The near-antisymmetry, $H_{ij} \approx -H_{ji}$ is reminiscent of journal bearings with a continuous film of incompressible fluid⁽⁵⁾. In fact, at time zero, when the gas is "trapped" by the sudden small displacement (so that $p_h = \text{constant}$ at each point in the bearing) the antisymmetry is exactly true.

For computer purposes, it is preferable to have the H_{ij} in analytical, rather than in tabular, form. Asymptotically, it may be expected that

$$H_i \rightarrow H_i(\infty) + (\text{constant})e^{-\alpha t}. \quad [5]$$




FIG.2-3. FORCE RESPONSE TO STEP-JUMP FOR AN INFINITELY LONG JOURNAL BEARING - H_{xx} AND H_{yy} VS. TIME




FIG. 2-4. FORCE RESPONSE TO STEP-JUMP FOR AN INFINITELY LONG JOURNAL BEARING - H_{yx} AND H_{xy} VS. TIME

To represent intermediate behavior, an expansion in LaGuerre's polynomials is used. These polynomials are chosen because they are orthogonal in the interval zero to infinity with a exponential weighting factor. As a consequence, the coefficients found for these polynomials are "best" in the least-squares sense.

They have the form:⁽⁶⁾

$$\begin{aligned} L_n(x) &= \sum_{k=0}^n \frac{n!}{(n-k)!k!} \frac{(-x)^k}{k!}, \\ L_0(x) &= 1, \\ L_1(x) &= 1 - x, \end{aligned} \quad [6]$$

and

$$\int_0^{\infty} e^{-x} L_n(x) L_m(x) dx = \delta_{mn}.$$

The series approximation:

$$H(t) - H(\infty) = \sum_{n=0}^{\infty} A_n L_n(\alpha t) e^{-\alpha t}, \quad [7]$$

is used. The coefficients A_n are determined by multiplication of both sides of this last equation by $L_m(\alpha x)$ and integrating. Thus

$$\begin{aligned} \int_0^{\infty} L_m(\alpha t) [H(t) - H(\infty)] dt &= \int_0^{\infty} \sum_{n=0}^{\infty} A_n L_n(\alpha t) L_m(\alpha t) e^{-\alpha t} dt \\ &= A_m / \alpha. \end{aligned} \quad [8]$$

Prior to the running of a linearized orbit, an accurate value of the attenuation coefficient " α " is not known and one must be guessed. Fortunately, a choice is not critical, inasmuch as any "error" in the guessed value will be absorbed by the LaGuerre coefficients. However, if the attenuation coefficient is optimally chosen, the coefficients of the LaGuerre series will approach zero most rapidly. To convert to a new attenuation coefficient, it is not necessary to rerun the orbit program. Instead, the following conversion relation can be used.

Thus:

$$\sum B_k L_k(\beta t) e^{-\beta t} = \sum A_k L_k(\alpha t) e^{-\alpha t}, \quad [9]$$

where:

$$B_j = \sum_{n=0}^j (-1)^{j+n} \frac{(\beta-\alpha)^{j-n}}{\alpha^{j+1}} \frac{\beta^{n+1}}{n! (j-n)!} A_n. \quad [10]$$

To approximate the results in Figures 2-3 and 2-4, an $\alpha = 1.0$ was used. When ten LaGuerre polynomials are used therewith, the numerical results are indetectibly different on the scale shown.

2.3 Stability Characteristics of the Infinitely Long Self-Acting Gas Journal Bearing

The foregoing theory was first applied to calculate the stability threshold of an infinitely long self-acting gas journal bearing operating with a steady load appropriate to $\epsilon = 0.6$, $\Lambda = 1.46$. Information on this geometry and operating condition is available from several sources^(2,7). The procedure for using the information from step-jump responses is straight forward. Dynamical equations are written in the form:

$$\begin{aligned} m\ddot{\delta x} &= \delta F_{xx} + \delta F_{yx}, \\ m\ddot{\delta y} &= \delta F_{xy} + \delta F_{yy}, \end{aligned} \quad [11]$$


with

$$\delta F_{yx} = H_{yx}(0) \delta y(t) + \int_0^t \delta y(\tau) \dot{H}_{yx}(t-\tau) d\tau \text{ etc.} \quad [12]$$


Typical initial conditions assumed in the present case were:

$$\begin{aligned} \delta x(0) &= -1 & \dot{\delta x}(0) &= 0 \\ \delta y(0) &= 0 & \dot{\delta y}(0) &= -1 \end{aligned}$$


The corresponding linearized orbits were computed numerically. Eventual growth of the displacements δx and δy was taken to indicate instability, with contrary results being taken to indicate stability. Figure 2-5 shows a linearized orbit deemed to be stable, Figure 2-6 shows one deemed to be marginally stable, and Figure 2-7 shows one deemed to be highly unstable. Physically, the difference between these cases lies in the mass associated with the shaft.



**FIG. 2-5. RESPONSE TO SMALL PERTURBATION ABOUT AN EQUILIBRIUM
 POSITION FOR INFINITELY LONG JOURNAL BEARING
 ORBIT PLOT OF SHAFT MASS CENTER COORDINATES**



**FIG.2-6. RESPONSE TO SMALL PERTURBATION ABOUT AN EQUILIBRIUM
 POSITION FOR INFINITELY LONG JOURNAL BEARING
 ORBIT PLOT OF SHAFT MASS CENTER COORDINATES**



**FIG. 2-7. RESPONSE TO SMALL PERTURBATION ABOUT AN EQUILIBRIUM
 POSITION FOR INFINITELY LONG JOURNAL BEARING
 ORBIT PLOT OF SHAFT MASS CENTER COORDINATES**

To remove as much as possible the personal judgement factor in setting the stability threshold, a growth factor was calculated from the orbit results. Asymptotically δy was assumed to possess the form:

$$\delta y(t) = Ae^{\beta t} \sin(\gamma t + \phi), \quad [13]$$

and the growth factor was computed from four successive values of δy (spaced by Δt).

Thus:

$$e^{2\beta\Delta t} = \frac{\delta y_3 \delta y_1 - \delta y_2^2}{\delta y_2 \delta y_0 - \delta y_1^2}. \quad [14]$$

The associated frequency " γ " was also of interest:

$$\cos(\gamma\Delta t) = \frac{\delta y_0 + \delta y_2 e^{-2\beta\Delta t}}{2 \delta y_1 e^{-\beta\Delta t}}. \quad [15]$$

Figure 2-8 shows the growth-rate found for the given operating condition $\epsilon = 0.6$, $\Lambda = 1.46$, and various values of dimensionless mass. The critical value of 2.17 converts to $\frac{MC \omega^2}{4\pi p^a L} = 0.831$. In Figure 2-9 this last value is compared with the results of Marsh and of Castelli and Elrod. The ratio of the critical value of " γ " as obtained from eq. [15] is compared in Figure 2-10 with Marsh's work. Agreement is excellent in each case.

Computer runs to provide individual points on the curve in Figure 2-8 can be performed very quickly (approx. 30 secs on a Univac - 1107 computer). Part of the speed achievable is due to a special integration procedure used in the convolution integral. To obviate the need for using data at every time step, a modified Gauss integration rule was adopted for which the locations and ordinate weighting factors W_i are given below.




FIG.2-8. SINGLE BEARING - TRANSLATIONAL STABILITY




FIG. 2-9. THE CRITICAL TRANSLATIONAL STABILITY RATIO, SINGLE BEARING, $L/D \rightarrow \infty$ (AFTER H. MARSH)




FIG. 2-10. THE TRANSLATIONAL CRITICAL FREQUENCY RATIO, SINGLE BEARING, $L/D \rightarrow \infty$ (AFTER H. MARSH)

$\frac{\pm X_i}{}$	$\frac{W_i}{}$
0	.197197636
8/40	.199459835
15/40	.139711837
19/40	.062229510

The rule is exact for sixth-degree polynomials and nearly exact for polynomials up to thirteenth degree. (For example, it gives $\int_0^1 x^{13} dx = 0.07136$ instead of 0.07143).

2.4 Stability Characteristics of a Two-Bearing System

To show the versatility of the new step-jump technique, a two-bearing system was next studied. This system was conceived to consist of two equally-loaded long bearings each similar to the single bearing discussed in Section 2.3. Figure 2-11 shows the geometrical arrangement and defines linear and angular coordinates appearing in the dynamical equations. The shaft rotates with angular velocities $(-\alpha_2, \alpha_1 \text{ and } \Omega)$ about the x, y and z) axes respectively through the shaft center of gravity and their time derivatives are of disturbance magnitude.

$$\begin{aligned} M\ddot{x}_M &= \delta F_{x,1} + \delta F_{x,2} , \\ M\ddot{y}_M &= \delta F_{y,1} + \delta F_{y,2} . \end{aligned} \quad [16]$$

Here $\delta_{x,1}$ represents the force in the x-direction on the shaft by bearing #1, etc. The average linear coordinates of the shaft within the bearings are:

$$\begin{aligned} \delta x_1 &= \delta x_M + L_1 \delta \alpha_1 & \delta x_2 &= \delta x_M - L_2 \delta \alpha_1 \\ \delta y_1 &= \delta y_M + L_1 \delta \alpha_2 & \delta y_2 &= \delta y_M - L_2 \delta \alpha_1 \end{aligned} \quad [17]$$

The separation of the bearings is presumed large enough to neglect the effects of conical misalignment on forces or torques. Therefore:

$$\begin{aligned}\delta F_{x,1} &= H_{xx}(o) \delta x_1(t) + \int_0^t \delta x_1(\tau) \dot{H}_{xx}(t - \tau) d\tau \\ &+ H_{yx}(o) \delta y_1(t) + \int_0^t \delta y_1(\tau) \dot{H}_{yx}(t - \tau) d\tau\end{aligned}\quad [18]$$

etc., where the H-functions here are the same as for the single bearing of section 2.3. The angular acceleration equation becomes:


$$\begin{aligned}I_T \ddot{\alpha}_1 &= I_p \dot{\Omega} \dot{\alpha}_2 + (L_1 \delta F_{x,1} - L_2 \delta F_{x,2}), \\ I_T \ddot{\alpha}_2 &= -I_p \dot{\Omega} \dot{\alpha}_1 + (L_2 \delta F_{y,2} - L_1 \delta F_{y,1}).\end{aligned}\quad [19]$$

Here I_T and I_p are the transverse polar moments of inertia.

For the brief, illustrative study of two-bearing stability, a system was taken which has marginal translational (as opposed to conical) stability. A dimensionless mass (as per Figure 2-8) of 2.0 was chosen. For large enough bearing separation, the results of Section 2.3 are duplicated. As the bearing locations are brought together, the immunity of the system to conical whirl is reduced and the conical stability threshold is transgressed. These features are illustrated by Figures 2-12 to 2-15.

For the response shown in Figures 2-12 and 2-13 the total bearing separation is 20, and the bearing system is stable in both the translational and conical modes. On the other hand, when the bearing separation is reduced to 4, all other operating conditions remaining fixed, the translational modes remain stable, while the conical modes become unstable. This fact is shown in Figures 2-14 and 2-15. Figure 2-16 shows the conical orbit of this unstable condition, and Figure 2-17 shows the determination of the stability threshold by means of a plot of bearing separation versus exponential growth factor. The critical bearing separation differs from that given by Marsh's approximate formula by less than 8%.

Listings of the digital computer programs used to implement the above analyses are given in Appendix A.



**FIG. 2-12. TRANSLATIONAL MOTION OF TWO BEARING SYSTEM
SHAFT MASS CENTER COORDINATES VS TIME**







FIG. 2-13. CONICAL MOTION OF TWO BEARING SYSTEM
 SHAFT ANGULAR COORDINATES VS TIME



**FIG. 2-14. TRANSLATIONAL MOTION OF TWO BEARING SYSTEM
SHAFT MASS CENTER COORDINATES VS TIME**



**FIG. 2-15. CONICAL MOTION OF TWO BEARING SYSTEM
SHAFT ANGULAR COORDINATES VS TIME**



**FIG. 2-16. CONICAL MOTION OF TWO BEARING SYSTEM
ANGULAR COORDINATES OF SHAFT — α_1 , VS. α_2**




FIG. 2-17. TWO BEARING SYSTEM—CRITICAL BEARING SEPARATION

3. CONCLUSIONS

The utility of Duhamel's method has been demonstrated for numerical investigations of stability and dynamics of bearing systems. This new "step-response" method complements bearing orbit-programs by permitting rapid parametric examinations of stability-in-the small. In many instances, the method would appear to be preferable to methods employing complex variable in that (a) computed quantities have easily interpreted physical counterparts and (b) the complexity of the procedure augments only slightly with system size.

4. RECOMMENDATIONS

1. As a consequent of the implementation of the step response method, it appears desirable to standardize sections of the analysis, such as the manner by which the response functions are obtained, the determination of the LaGuerre coefficients, the optimization of the attenuation factor, etc. so that these sections can be used as library routines for other types of bearing configurations.

2. The method described in this report should be used to study the stability of other types of bearings. In particular, the externally pressurized thrust bearing and hybrid journal bearings. With the appropriate organization of the component parts of the analysis, the stability analysis of these more complex bearings can be done in a straight forward manner.

REFERENCES

1. Licht, L. and Elrod, H. G., Jr., *An Analytical and Experimental Study of the Stability of Externally-Pressurized, Gas-Lubricated Thrust Bearings*, FIRL Interim Report I-A2049-12 Contract Nonr-2342(00) Task NR061-113 Administered by Office of Naval Research, Dept. of the Navy.
2. Castelli, V. and Elrod, H. G., Jr., *Solution of the Stability Problem for 360 Deg. Self-Acting Gas-Lubricated Bearings*, ASME paper No. 64-LubS-10.
3. McCabe, J. T., Shapiro, W., and Chu, T. Y., *The Analysis and Design of a Gas Bearing System for a Brayton Cycle Turbine-Compressor*, FIRL Final Report F-B2250 to Pratt and Whitney Aircraft.
4. Churchill, R. V., *Modern Operational Mathematics in Engineering*, McGraw-Hill, 1944.
5. Reddi, M and Trumpler, P., *Stability of the High Speed Journal Bearing Under Steady Load*, Journal of Eng. for Industry, Trans. of the ASME, Vol. 84, Series B No. 3, 1962.
6. *Handbook of Mathematical Functions with Formulas, Graphs, and Mathematical Tables*, National Bureau of Standards, Applied Math. Series 55, U.S. Government Printing Office, Washington, D.C. 1964.
7. Marsh, H., *The Stability of Aerodynamic Gas Bearings*, Mech. Eng. Science Monograph No. 2, Institute of Mech. Eng. Westminster, England, 1965.

APPENDIX A
Fortran Program Listings

The program used to produce the LaGuerre coefficient (ROSIE) for a long, plane journal bearing was compiled on an IBM 7094 in FORTRAN IV and uses "NAMELIST" for input. This program is an adaption from a more generalized program and, as a consequence, has certain input that are not applicable for the type of problem treated in this report

ROSIE contains the following routines:

MAIN

SUBROUTINE CUREAL (KAY)

SUBROUTINE SET 1

SUBROUTINE ALFA (KK)

SUBROUTINE FILM

SUBROUTINE FORCE (K)

SUBROUTING QQQ

FUNCTION ALAGER (N, ALPHAT)

The MAIN program require the following input in NAMELIST form :

SXM = 0.0

SYM = eccentricity

SA1 = 0.0 } no shaft rotation
SA2 = 0.0 }

SB1 = 0.0 } no bearing rotation
SB2 = 0.0 }

M = no. of circumferential grid intervals

N = no. of axial grid intervals

PLAMDA = $\frac{6\mu\omega}{p_a} \left(\frac{R}{C}\right)^2$

ROVL = R/L

DT = time step

TMAX = maximum allowable no. of time steps before termination

INF = FALSE

ORDER = order of the LaGuerre Poly. (an integer)

ALPHA = the attenuation constant " α "

NK = 3

NCASE = case no. (an integer)

SUBROUTINE CUREAL is specially written for each type of problem and contains a specification for the step-displacement from equilibrium; DELDEG is the size of the step taken.

For each degree of freedom, the LaGuerre coefficient are punched out in a loop which goes from $K = 1$, ORDER. The information on each card is

K, ORDER, XM, YM, AX(K), AY(K),

where XM and YM are the coordinates; AX and AY are the coefficient representing the forces in the X and Y directions. The FORMAT is

2I3, 2F7.3, 2E18.8, 26 X 2H\$P

The Dynamics program which reads the punched card output listed above was compiled in FORTRAN IV on a UNIVAC 1107. The routines used are

ELRO (Main program)

SUBROUTINE LAGUER

FUNCTION ALAGER (N, ALPHAT)

The input consist of

1. READ:NDEG, NORDER, KSTEP, ALPHA

FORMAT 3I6, F10.0

where

NDEG = no. of degrees of freedom (2)

NORDER = order of LaGuerre polynomial

KSTEP = the interval at which the growth factors are to be printed out (10)

2. For each degree of freedom:

READ: punched card output described above

3. READ: $(H(\infty)_{ij}, i = 1,2) J = 1,2)$

FORMAT 4E15.8

(this input must be punched from printed output of coefficient program)

4. READ:NT, NTMAX, DELTAT

FORMAT 2I6, F10.0

where

NT = integration interval
 NTMAX = maximum no. of time steps
 DELTAT = the time step DT x NT
 5. READ:KLUE, AMASS, EL1, EL2, TRANSI, POLARI, ASYMM
 FORMAT I6, 6F10.0

where

KLUE = 1, go back to point 5 READ
 = 2, go back to point 4 READ
 = 3, Stop
 AMASS = shaft mass (non-dimensional) $\frac{MC \Omega^2}{4 p_a RL}$
 EL1, EL2 = distance from shaft mass center to center line of brg, 1
 and 2 divided by length of bearing
 TRANSI, POLARI = shaft transverse and polar moment of inertia (non-
 dimensional

$$\left. \begin{array}{l} I_T \\ I_P \end{array} \right\} \frac{C \Omega^2}{4 p_a RL^3}$$

ASYMM = initial displacement of brg. 1 relative to brg. 2

The program listings follow.

```

COMMON SYM,SYM,SA1,SA2,SR1,SR2,T,M,N,M1,M2,NN,DTHE,DETA,XM,YM,A1,
1      A2,R1,R2,H[63,17],S[63],C[63],HTHE[63,17],HETA[63,17],
2      Q[63,17],PLAMDA,RROVLL,DT,QQ[63,17],TMAX,INF,EQ[63,17],
3      P[63,17],FORCEFX[51],FORCEY[51],TORKY[51],TORKY[51],ORDER,
4      ALPHA,AX[20],AY[20],AXZ[20],AYZ[20],AINF[20],NK,KLUE,
5      DFLDEG,KOUNT
COMMON/FACTOR/FE,FFE,FFFF,FFFFF
LOGICAL FAIL,PASS,INF
INTEGER OUT,ORDER
NAMELIST/INPUT/SYM,SYM,SA1,SA2,SR1,SR2,M,N,          PLAMDA,ROVL,DT,
1 TMAX,INF,ORDER,ALPHA,NK,NCASE
IN=5
OUT=6
KAY=1
FAIL = .FALSE.
PASS = .FALSE.
KLUE=1
10 READ(IN,INPUT)
WRITE(OUT,1)
1 FORMAT(1H1)
WRITE(OUT,INPUT)
RROVLL = ROVL**2
CALL SET1
CALL FILM
FE = .5/DTHE
FFE = 1./DTHE**2
FFFF = .5/DETA
FFFFF = 1./DETA**2
DO 15 I=M1,M2
Q[I,1] = H[I,1]
15 Q[I,NN] = H[I,NN]
IF(FAIL) GO TO 200
IF(PASS) GO TO 25
DO 20 J=M1,M2
DO 20 J=2,N
20 Q[I,J] = H[I,J]
IK=1
25 CONTINUE
DO 30 J=2,N
Q[I,J]=Q[M+1,J]
30 Q[M+3,J]=Q[3,J]
IF(INF) GO TO 35
GO TO 34
35 DO 36 J=M1,M2
Q[I,1] = Q[I,2]
36 Q[I,NN] = Q[I,N]
34 CALL QQQ
IF (FAIL) GO TO 200
IF(T .LE. TMAX) GO TO 40
GO TO 50
40 T = T+DT
42 FORMAT(7F15.7)
IK=IK+1
GO TO 25
50 DO 60 J=M1,M2
DO 60 J=1,NN

```

```

KS=1
CALL FORCE[KS]
WRITE(OUT,16) T
WRITE(OUT,42) ([P(I,J),J=1,17],I=1,39)
WRITE(OUT,61) FORCEX[1],FORCEY[1],TORKX[1],TORKY[1]
61 FORMAT(19H EQUILIBRIUM FORCES // 5X 4F18.8)
70 CALL SFT1
CALL CURFAL[KAY]
72 GO TO (71,10,150),KLUF
71 IF(PASS) GO TO 90
DO 80 I=M1,M2
DO 80 J=1,NN
80 Q(I,J)=FQ(I,J)
90 CALL FILM
DO 92 I=M1,M2
Q(I,1)=H(I,1)
92 Q(I,NN)=H(I,NN)
91 DO 100 ITER=1,50
DO 95 J=2,N
Q(I,J)=Q(M+1,J)
95 Q(M+3,J)=Q(3,J)
IF(INEF) GO TO 97
GO TO 98
97 DO 96 J=M1,M2
Q(I,1)=Q(I,2)
96 Q(I,NN)=Q(I,N)
98 CALL QCG
IF (FAIL) GO TO 200
CALL FORCE[ITER]
CALL ALFA[ITER]
100 T=T+DT
WRITE(OUT,105)
105 FORMAT(1H1 3X 1HT 12X 6HFORCEX 12X 6HFORCEY 13X 5HTORKX 13X
1 5HTORKY )
WRITE(OUT,16) T
16 FORMAT (F15.8)
DO 110 L=1,50
LL= 50*(KOUNT-1)+1
110 WRITE(OUT,111) LL,FQCEX[LL],FORCEY[LL],TORKX[LL],TORKY[LL]
111 FORMAT(1X 14,4F18.8)
WRITE(OUT,120)
120 FORMAT(1H1 50X 20HLAGUER COEFFICIENTS // 5X 1HT 16X 2HAX 16X 2HAY
115X 3HAX7 15X 3HAY7 14X 4HAINF)
DO 130 L=1,ORDER
130 WRITE(OUT,131) LL,AX[LL],AY[LL],AXZ[LL],AYZ[LL],AINF[LL]
131 FORMAT(2X 14,5F18.8)
KOUNT = KOUNT + 1
IF(T .LE. TMAX) GO TO 91
KAY=KAY+1
XX= ALPHA/DELNEG
DO 160 K=1,ORDER
AX(K)=[AY(K)-AINF(K)+FORCEX(50)]*XX
AY(K)=[AY(K)-AINF(K)+FORCEY(50)]*XX
WRITE(OUT,161) K,ORDER,YM,YM,AX(K),AY(K)
161 FORMAT(2I3,2F7.3,2F18.8,26X 2HSP )
AX7(K)=[AXZ(K)-AINF(K)+TORKX(50)]*XX

```



```

WRITE(OUT,120)
DO 170 L=1,ORDER
170 WRITE(OUT,131)LL,AX[1],AY[1],AXZ[1],AYZ[1],AINF[1]
IF(KAY .LE. NK) GO TO 70
WRITE(OUT,140) KAY
140 FORMAT(1Y4WKAY= 14, 6H GOOD )
200 WRITE(OUT,201)NCASE
201 FORMAT(4BX21)CLEAR, ZERO ,CASE NO. 15 )
150 STOP
END

$IRETC KUREAL 11ST,SDD
SUBROUTINE CUREAL(KAY)
COMMON SYM,SYM,SA1,SA2,SR1,SR2,T,M,N,M1,M2,NN,DTHE,DETA,XM,YM,A1,
1 A2,R1,R2,H[63,17],S[63],C[63],HTHE[63,17],HETA[63,17],
2 Q[63,17],PIAMDA,RROVLL,DT,QO[63,17],TMAX,INF,EQ[63,17],
3 P[63,17],FORCEX[51],FORCEY[51],TORKX[51],TORKY[51],ORDER,
4 ALPHA,AX[20],AY[20],AXZ[20],AYZ[20],AINF[20],NK,KLUE,
5 DELDEG,KOUNT
LOGICAL FAIL,PASS,INF
INTEGER OUT,ORDER
GO TO (1,2,3,4,5,6),KAY
1 KLUE = 1
YM=.7
DELDEG=.1
TMAX=4.7124
GO TO 100
2 KLUE = 1
YM=.1
DELDEG=.1
GO TO 100
3 KLUE = 3
GO TO 100
4 CONTINUE
5 CONTINUE
6 CONTINUE
100 RETURN
END

$IRETC SSET1
SUBROUTINE SET1
COMMON SYM,SYM,SA1,SA2,SR1,SR2,T,M,N,M1,M2,NN,DTHE,DETA,XM,YM,A1,
1 A2,R1,R2,H[63,17],S[63],C[63],HTHE[63,17],HETA[63,17],
2 Q[63,17],PIAMDA,RROVLL,DT,QO[63,17],TMAX,INF,EQ[63,17],
3 P[63,17],FORCEX[51],FORCEY[51],TORKX[51],TORKY[51],ORDER,
4 ALPHA,AX[20],AY[20],AXZ[20],AYZ[20],AINF[20],NK,KLUE,
5 DELDEG,KOUNT
LOGICAL FAIL,PASS,INF
INTEGER OUT,ORDER
XM = SYM
YM = SYM
A1 = SA1
A2 = SA2
R1 = SR1
R2 = SR2
T = 0.
KOUNT = 1
DO 10 K=1,ORDER

```

```

      AY[K]=0.0
      AX7[K]=0.0
      AY7[K]=0.0
10  AINF[K]=0.0
      RETURN
      END

SIRFTC AALFA LIST,SDD
      SUBROUTINE ALFA(KK)
      COMMON SYM,SYM,SA1,SA2,SR1,SR2,T,M,N,M1,M2,NN,DTHE,DETA,XM,YM,A1,
1      A2,R1,R2,H[63,17],S[63],C[63],HTHF[63,17],HETA[63,17],
2      Q[63,17],PIAMDA,RROVLL,DT,QQ[63,17],TMAX,INF,EQ[63,17],
3      P[63,17],FORCEX[51],FORCEY[51],TORKX[51],TORKY[51],ORDER,
4      ALPHA,AX[20],AY[20],AXZ[20],AYZ[20],AINF[20],NK,KLUF,
5      DELDEG,KOUNT
      LOGICAL FAIL,PASS,INF
      INTEGER OUT,ORDER
      ALPHAT = ALPHA*T
      DO 10 K=1,ORDER
      POLYN = ALAGFR[K-1,ALPHAT]
      AX[K] = AX[K] + DT*POLYN*FORCEX[KK]
      AY[K] = AY[K] + DT*POLYN*FORCEY[KK]
      AX7[K] = AX7[K]+DT*POLYN*TORKX[KK]
      AY7[K] = AY7[K]+DT*POLYN*TORKY[KK]
10  AINF[K] = AINF[K]+DT*POLYN
      RETURN
      END

SIRFTC FFILM LIST,SDD
      SUBROUTINE FILM
      COMMON SYM,SYM,SA1,SA2,SR1,SR2,T,M,N,M1,M2,NN,DTHE,DETA,XM,YM,A1,
1      A2,R1,R2,H[63,17],S[63],C[63],HTHF[63,17],HETA[63,17],
2      Q[63,17],PIAMDA,RROVLL,DT,QQ[63,17],TMAX,INF,EQ[63,17],
3      P[63,17],FORCEX[51],FORCEY[51],TORKX[51],TORKY[51],ORDER,
4      ALPHA,AX[20],AY[20],AXZ[20],AYZ[20],AINF[20],NK,KLUF,
5      DELDEG,KOUNT
      LOGICAL FAIL,PASS,INF
      INTEGER OUT,ORDER
      PIF = 3.14159265
      RAD = PIF/180.0
      DTHE = 360.0*RAD/FLOAT(M)
      DETA = 1.0/FLOAT(N)
      M1=2
      M2=M+2
      NN=N+1
      DO 10 J=1,NN
      Z = -.5 +FLOAT[J-1]*DETA
      XPRIM = XM + [A1-R1]*Z
      YPRIM = YM + [A2-R2]*Z
      DO 10 I=M1,M2
      ARG = DTHE*FLOAT[I-M1]
      S[I]=SIN(ARG)
      C[I]=COS(ARG)
      H[I,J] = 1.0 + XPRIM*S[I] + YPRIM*C[I]
      IF(H[I,J].LE. 0.01 GO TO 20
      HTHF[I,J] = XPRIM*C[I] - YPRIM*S[I]
10  HETA[I,J] = [A1-R1]*S[I] + [A2-R2]*C[I]
30  RETURN

```

```

RETURN
END
$IRFIC FFORCE LIST,SDO
SURROUTINE FORCE[K]
DIMENSION SAV1[5],SAV2[5],SAV3[5],SAV4[5]
COMMON SYM,SYM,SA1,SA2,SR1,SR2,T,M,N,M1,M2,NN,DTHE,DETA,XM,YM,A1,
1      A2,R1,R2,H[63,17],S[63],C[63],HTHE[63,17],HETA[63,17],
2      Q[63,17],PIAMDA,RROVLL,DT,QO[63,17],TMAX,INF,EQ[63,17],
3      P[63,17],FORCEX[51],FORCEY[51],TORKX[51],TORKY[51],ORDER,
4      ALPHA,AX[20],AY[20],AXZ[20],AYZ[20],AINF[20],NK,KLUE,
5      DELDEG,KOUNT
LOGICAL FAIL,PASS,INF
INTEGER OUT,ORDER
DO 20 J=1,NN
  SX=0.0
  SY=0.0
  SX7=0.0
  SY7=0.0
  Z = -.5 + FLOAT(J-1)*DETA
  MN=M+1
  DO 10 I=M1,MN
    P[I,J] = Q[I,J]/H[I,J]
    SX = SX + P[I,J]*S[I]*DTHE
    SY = SY + P[I,J]*C[I]*DTHE
    SX7 = Z*SX
10  SY7 = Z*SY
    IF(J.EQ.1) GO TO 30
    DZ = DETA
    GO TO 40
30  DZ = 0.0
40  FORCEX[K] = CLCINT[1,DZ,SX,SAV1]
    FORCEY[K] = CLCINT[1,DZ,SY,SAV2]
    TORKX[K] = CLCINT[1,DZ,SX7,SAV3]
    TORKY[K] = CLCINT[1,DZ,SY7,SAV4]
20  CONTINUE
RETURN
END

```

```

$IRFIC Q7A LIST,SDO
SURROUTINE QOO
COMMON SYM,SYM,SA1,SA2,SR1,SR2,T,M,N,M1,M2,NN,DTHE,DETA,XM,YM,A1,
1      A2,R1,R2,H[63,17],S[63],C[63],HTHE[63,17],HETA[63,17],
2      Q[63,17],PIAMDA,RROVLL,DT,QO[63,17],TMAX,INF,EQ[63,17],
3      P[63,17],FORCEX[51],FORCEY[51],TORKX[51],TORKY[51],ORDER,
4      ALPHA,AX[20],AY[20],AXZ[20],AYZ[20],AINF[20],NK,KLUE,
5      DELDEG,KOUNT
COMMON/FACTOR/FE,FFE,FFFF,FFFFF
LOGICAL FAIL,PASS,INF
INTEGER OUT,ORDER
DO 10 I=M1,M2
DO 10 J=2,N
  QT=[Q[I+1,J]-Q[I-1,J]]*FE
  QTT = [Q[I+1,J]+Q[I-1,J]-2.*Q[I,J]]*FFE
  QZ = [Q[I,J+1]-Q[I,J-1]]*FFFF
  QZ7 = [Q[I,J+1] + Q[I,J-1]-2.*Q[I,J]]*FFFFF
  DQ = - QT + [Q[I,J]*I-Q[I,J]*[1.0-H[I,J]]+H[I,J]*QTT-QT*HTHE[I,J]
1  +RROVLL*[QZ7+H[I,J]-QZ*HETA[I,J]]+H[I,J]*[QT*2+RROVLL*

```

```

      2      Q7**2))/PLAMDA
      Q0(I,J) = Q(I,J)+Q0*DT
      IF(Q0(I,J) .GT. 100.1 GO TO 25
10  CONTINUE
      DO 20 I = M1,M2
      DO 20 J = 2,N
      20  Q(I,J) = Q0(I,J)
      21  RETURN
      25  WRITE(OUT,26)
      26  FORMAT(9H BLOW UP 1
      FAIL = .TRUE.
      RETURN
      END
SIRFTC LAG      LIST.SDD
      FUNCTION ALAGER(N,ALPHAT)
      S=1.0
      NN=N+1
      DO 10 K=1,NN
      S=-S*ALPHAT*FLOAT(N-K+1)/FLOAT(K*K)
10  ALAGER=ALAGER+S
      RETURN

```

```

FLT FLR0.1,660406, 41048
COMMON SX[2],SDX[2],X[4,1000],DEX[4,1000],NDX[2],H[2,2,100],
1 HDWT4[2,2],HDWT5[2,2],HDWT6[2,2],HDWT7[2,2],
1 DELTAT,A[2,2,10],HINF[2,2],AX[10],AY[10],NT,ALPHA,NT,
2 NDEG,NORDER,HDOT[2,2,100],HDWT1[2,2],HDWT2[2,2],HDWT3[2,2]
3,SUM[4],XM[1000],YM[1000],ALPHA1[1000],ALPHA2[1000]
1,RETA[4]
COMMON MK1,MK2,MK3,MK4,MK5,MK6,MK7
READ[5,10]NDEG,NORDER,KSTEP,ALPHA
10 FORMAT(3I6,F10.0)
DO 20 J = 1,NDEG
DO 20 I = 1,10
READ[5,11] K0,OQ,X0,Y0,AX[K0],AY[K0]
11 FORMAT(2I3,2F7.3,2F18.8)
A[J,1,I] = AX[I]
20 A[J,2,I] = AY[I]
READ[5,15] [(HINF[J,I],I=1,2),J=1,2]
15 FORMAT(4F15.8)
WRITE[6,23] [(HINF[J,I],I=1,2),J=1,2]
23 FORMAT(24H HINF 1,1 1,2 2,1 2,2 = 4F18.8 )
WRITE[6,19]
19 FORMAT(//6H ORDER6X 6HA[1,1], 12X 6HA[1,2], 12X 6HA[2,1], 12X
16HA[2,2] / )
DO 21 N=1,NORDER
21 WRITE[6,22] N,A[1,1,N],A[1,2,N],A[2,1,N],A[2,2,N]
22 FORMAT(2X I2, 4F18.8)
400 READ[5,410] NT,NTMAX,DELTAT
410 FORMAT(2I6,F10.0)
FTMAX = NTMAX
FNT = NT
NNTT=NT+5
NT = DELTAT/FNT
30 READ[5,13]KLUE,AMASS,FL1,EL2,TRANSI,POLARI,ASYMM
13 FORMAT(16,6F10.0)
FL=FL1+EL2
WRITE[6,9]NDEG,NT,DT,NORDER,NTMAX,ALPHA,KLUE,AMASS,POLARI,TRANSI,
1 FL1,EL2,ASYMM
9 FORMAT(26H NO. OF DEG. OF FREEDOM = 12//23H INTEGRATION INTERVAL =
113,16H WITH TIME STEP F15.8 // 23H LAGUERRE POLY ORDER = 12,
212H MAX TIME = 14. 10H ALPHA = F15.8,9H KLUE = 11//8H MASS =
3F15.8,5X 9HPOLARI = F15.8,5X 9HTRANSI = F15.8//
4 6HFL1 = F15.8, 5X 6HFL2 = F15.8, 5X 8HASYMM = F15.8//)
READ[5,12] [SX[K],SDX[K],K=1,NDEG]
12 FORMAT(4F12.0)
DO 50 I=1,NDEG
NTT = NT+1
DO 60 L=1,NTT
X[I,1] = SX[I]
X[I+2,L]=SX[I]+ASYMM
DEX[I+2,L]=0.0
60 DEX[I,L] = 0.0
DEX[I+2,1]=SDX[I]
50 DEX[I,1] = SDX[I]
DXM=FL2*DEX[1,1]/FL+FL1*DEX[3,1]/EL
DYM = FL2*DEX[2,1]/EL + FL1*DEX[4,1]/EL
DALPH1=(DEX[1,1]-DEX[3,1])/EL
DALPH2=(DEX[2,1]-DEX[4,1])/EL

```

```

DO 51 L=1,NTY
  YM(L)=FL2*X(1,1)/EL+FL1*X(3,1)/EL
  YM(L)=FL2*X(2,1)/EL+FL1*X(4,1)/EL
  ALPHA1(L)=(X(1,1)-X(3,1))/FL
51 ALPHA2(L)=(X(2,1)-X(4,1))/FL
  T= 0.0
  N1=1
  N2=50
  L=NT+1
  KINT=NT/40
  K1=KINT
  K2=5*KINT
  K3=12*KINT
  K4=20*KINT
  K5=28*KINT
  K6=35*KINT
  K7=39*KINT
  MK1 = K1+1
  MK2 = K2+1
  MK3 = K3+1
  MK4=K4+1
  MK5=K5+1
  MK6=K6+1
  MK7=K7+1
  CALL LAGUER
  DDELT=DEL TAT*DT
  WRITE(6,1000)
1000 FORMAT(//4H   LBY 7HWD(1,1), 12X 7HWD(1,2), 12X 7HWD(2,1), 12X
1      7HWD(2,2) / )
  DO 1001 K=1,NT
1001 WRITE(6,1002) K,HDOT(1,1,K),HDOT(1,2,K),HDOT(2,1,K),HDOT(2,2,K)
1002 FORMAT(2X I2, 4F18.8)
  DO 80 I=1,NDEG
  DO 80 J=1,NDEG
    HDWT1(I,J) = HDOT(I,J,MK1)*DDELT*.06222951
    HDWT2(I,J)= HDOT(I,J,MK2)*DDELT * .13971184
    HDWT3(I,J) = HDOT(I,J,MK3) * DDELT*.19945984
    HDWT4(I,J)=HDOT(I,J,MK4)*DDELT*.19719764
    HDWT5(I,J)=HDOT(I,J,MK5)*DDELT*.19945983
    HDWT6(I,J)=HDOT(I,J,MK6)*DDELT*.13971184
    HDWT7(I,J)=HDOT(I,J,MK7)*DDELT*.06222950
    H(I,J,1) = (H(I,J,1)+HINF(I,J))*DT
80 CONTINUE
95 LK1 = L-K1
  LK2 = L-K2
  LK3 = L-K3
  LK4=L-K4
  LK5=L-K5
  LK6=L-K6
  LK7=L-K7
  DO 210 I=1,NDEG
    SUM(I)=0.0
    SUM(I+2)=0.0
  DO 150 J=1,NDEG
    SUM(I)=SUM(I)+X(J,LK1)*HDWT1(J,I)+
1X(J,LK2)*HDWT2(J,I)+
1X(J,LK3)*HDWT3(J,I)+

```

```

1X(J,LK4)*HDWT4(J,I)+
1X(J,LK5)*HDWT5(J,I)+
1X(J,LK6)*HDWT6(J,I)+
1X(J,LK7)*HDWT7(J,I)+
1X(J,I)*H(J,I,1)
SUM(I+2)=SUM(I+2)+X(J+2,LK1)*HDWT1(J,I)+
1X(J+2,LK2)*HDWT2(J,I)+
1X(J+2,LK3)*HDWT3(J,I)+
1X(J+2,LK4)*HDWT4(J,I)+
1X(J+2,LK5)*HDWT5(J,I)+
1X(J+2,LK6)*HDWT6(J,I)+
1X(J+2,LK7)*HDWT7(J,I)+
1X(J+2,I)*H(J,I,1)
150 CONTINUE
210 CONTINUE
DXMNU=DXM+(SUM(1)+SUM(3))/AMASS
YM(L+1)=YM(L)+.5*(DXMNU+DXM)*DT
DYMNU=DYM+(SUM(2)+SUM(4))/AMASS
YM(L+1)=YM(L)+.5*(DYMNU+DYM)*DT
DANU1=DALPH1 + (POLAR)*2.0*DALPH2*DT+EI1*SUM(1)-FL2*SUM(3)/TRANSI
ALPHA1(L+1)=ALPHA1(L)+DT*(DANU1+DALPH1)*.5
DANU2=DALPH2+(-POLAR)*2.0*DALPH1*DT+FL1*SUM(2)-EL2*SUM(4)/TRANSI
ALPHA2(L+1)=ALPHA2(L)+DT*(DANU2+DALPH2)*.5
DXM=DXMNU
DYM=DYMNU
DALPH1=DANU1
DALPH2=DANU2
L = L + 1
Y(1,L)=XM(L)+FL1*ALPHA1(L)
X(2,L)=YM(L)+FL1*ALPHA2(L)
Y(3,L)=XM(L)-FL2*ALPHA1(L)
X(4,L)=YM(L)-FL2*ALPHA2(L)
T = T + DT
IF(L/50*50-L.EQ.0.OR.L.GE.NTMAX) GO TO 320
GO TO 95
320 WRITE(6,311)
311 FORMAT(1H1 15X 4HSTEP 12X 2HXM 18X 2HYM 15X 6HALPHA1 14X 6HALPHA2)
DO 350 K = N1,N2
IF([K/KSTEP*KSTEP-K.EQ.0].AND.[K.GE.NNTT.AND.K.LE.NTMAX])GO TO 700
GO TO 705
700 Q1=[YM(K-1)*XM(K-3)-YM(K-2)**2]/[XM(K)*XM(K-2)-XM(K-1)**2]
Q2=[YM(K-1)*YM(K-3)-YM(K-2)**2]/[YM(K)*YM(K-2)-YM(K-1)**2]
Q3=[ALPHA1(K-1)*ALPHA1(K-3)-ALPHA1(K-2)**2]/
1[ALPHA1(K)*ALPHA1(K-2)-ALPHA1(K-1)**2]
Q4=[ALPHA2(K-1)*ALPHA2(K-3)-ALPHA2(K-2)**2]/
1[ALPHA2(K)*ALPHA2(K-2)-ALPHA2(K-1)**2]
IF(Q1.GT.0.0) RETAXM=-ALOG(Q1)/(2.*DT)
IF(Q2.GT.0.0) RETAYM=-ALOG(Q2)/(2.*DT)
IF(Q3.GT.0.0) RETA1=-ALOG(Q3)/(2.*DT)
IF(Q4.GT.0.0) RETA2=-ALOG(Q4)/(2.*DT)
Y0Y= XM(K-3)*EXP(RETAXM*( 3.*DT))
Y1Y= XM(K-2)*EXP(RETAXM*( 2.*DT))
Y2Y= XM(K-1)*EXP(RETAXM*( DT))
Y0Y= YM(K-3)*EXP(RETAYM*( 3.*DT))
Y1Y= YM(K-2)*EXP(RETAYM*( 2.*DT))
Y2Y= YM(K-1)*EXP(RETAYM*( DT))

```

```

Y1A1 = ALPHA1*(K-2)*EXP(BETA1*( 2.*DT))
Y2A1 = ALPHA1*(K-1)*EXP(BETA1*( DT))
Y0A2 = ALPHA2*(K-3)*EXP(BETA2*( 3.*DT))
Y1A2 = ALPHA2*(K-2)*EXP(BETA2*( 2.*DT))
Y2A2 = ALPHA2*(K-1)*EXP(BETA2*( DT))
ARG1 = (Y0X+Y2X)/(2.*Y1X)
ARG2 = (Y0Y+Y2Y)/(2.*Y1Y)
ARG3 = (Y0A1 + Y2A1)/(2.*Y1A1)
ARG4 = (Y0A2 + Y2A2)/(2.*Y1A2)
IF(ARG1 .GE. 1. .OR. ARG2 .GE. 1.) GO TO 712
IF(ARG3 .GE. 1. .OR. ARG4 .GE. 1.) GO TO 712
GAMMAX=ACOS(ARG1)/DT
GAMMAY=ACOS(ARG2)/DT
GAMA1=ACOS(ARG3)/DT
GAMA2=ACOS(ARG4)/DT
GO TO 710
712 GAMMAX = 0.
    GAMMAY = 0.
    GAMA1 = 0.
    GAMA2 = 0.
710 WRITE(6,711)K,BETAXM,BETAYM,BETA1,BETA2,GAMMAX,GAMMAY,GAMA1,GAMA2
711 FORMAT(5Y12H)TIME STEP = 13/10X 18HGROWTH FACTOR X = E15.8/10X
    1 18HGROWTH FACTOR Y = E15.8/10X 23HGROWTH FACTOR ALPHA1 = E15.8/
    210X 23HGROWTH FACTOR ALPHA2 = E15.8/10X 9HFREQ X = E15.8,
    310X 9HFREQ Y = E15.8/10X10HFREQ A1 = E15.8,10X10HFREQ A2 = E15.81
705 WRITE(6,312)K,XM(K),YM(K),ALPHA1(K),ALPHA2(K)
350 CONTINUE
312 FORMAT(15X 14,4F20.8)
    N1 = N1 + 50
    N2 = N2 + 50
    IF( L.GT. NTMAX) GO TO 500
    GO TO 95
500 GO TO (30,400,600),KLUF
600 STOP
END
ELT DLAGUE,1,660303, 36641
SUBROUTINE LAGUER

```

C

```

COMMON SX(2),SDX(2),X(4,1000),DEX(4,1000),NDX(2),H(2,2,100),
1 HDWT4(2,2),HDWT5(2,2),HDWT6(2,2),HDWT7(2,2),
1 DELTAT,A(2,2,10),HINF(2,2),AX(10),AY(10),NT,ALPHA,DT,
2 NDEFG,NORDER,HDOT(2,2,100),HDWT1(2,2),HDWT2(2,2),HDWT3(2,2)
3,SUM(4),XM(1000),YM(1000),ALPHA1(1000),ALPHA2(1000)
1,BETA(4)
COMMON MK1,MK2,MK3,MK4,MK5,MK6,MK7
KORDER = NORDER-1
DO 100 LL=1,8
GO TO (1,2,3,4,5,6,7,8),LL
1 L=1
GO TO 9
2 L=MK1
GO TO 9
3 L=MK2
GO TO 9
4 L=MK3
GO TO 9

```



```

5 L=MK4
GO TO 0
6 L=MK5
GO TO 0
7 L=MK6
GO TO 0
8 L=MK7
9 TT=FLOAT(L-1)*DT
ALPHAT = ALPHA*TT
DO 80 I=1,NDEG
DO 80 J=1,NDEG
HH=0.0
DO 50 K=1,NORDER
POLYN = ALAGER(K-1,ALPHAT)
50 HH = HH+POLYN*A[I,J,K]
H[I,J,L] = HH*EXP(-ALPHAT)
80 CONTINUE
ALPHAT = ALPHAT+.00001
DO 200 I=1,NDEG
DO 200 J=1,NDEG
HD = 0.0
DO 250 K=1,KORDER
250 HD=HD+A[I,J,K+1]*FLOAT(K)*[ALAGER(K,ALPHAT)-ALAGER(K-1,ALPHAT)]
1 /ALPHAT
HDOT[I,J,L] = ALPHA*(HD*EXP(-ALPHAT)-H[I,J,L])
200 CONTINUE
100 CONTINUE
WRITE(6,110)
110 FORMAT(/4H 18X 6HH[1,1], 12X 6HH[1,2], 12X 6HH[2,1], 12X
1 6HH[2,2] / )
DO 120 L=1,NT
120 WRITE(6,121) L,H[1,1,L],H[1,2,L],H[2,1,L],H[2,2,L]
121 FORMAT(2X I2, 4F18.8)
RETURN
END
ELT ALAGER,1,651230, 34045
FUNCTION ALAGER(N,ALPHAT)
S=1.0
ALAGER=1.0
NN=N+1
DO 10 K=1,NN
S=S*ALPHAT*FLOAT(N-K+1)/FLOAT(K*K)
10 ALAGER=ALAGER+S
RETURN
END

```

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) The Franklin Institute Research Laboratories 20th and the Benjamin Franklin Parkway Philadelphia, Pennsylvania 19103		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b. GROUP None	
3. REPORT TITLE DETERMINATION OF GAS BEARING STABILITY BY RESPONSE TO A STEP-JUMP			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Interim Report July, 1966			
5. AUTHOR(S) (Last name, first name, initial) Elrod, Jr., H. G.; McCabe, J. T.; Chu, T. Y.			
6. REPORT DATE July, 1966		7a. TOTAL NO. OF PAGES 56	7b. NO. OF REFS 7
8a. CONTRACT OR GRANT NO. Nonr-2342(00)		9a. ORIGINATOR'S REPORT NUMBER(S) I-A2049-27	
b. PROJECT NO. Task NR 062-316		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
c. d.			
10. AVAILABILITY/LIMITATION NOTICES Reproduction in Whole or in Part is Permitted for any Purpose of the U.S. Government.			
11. SUPPLEMENTARY NOTES ---		12. SPONSORING MILITARY ACTIVITY ---	
13. ABSTRACT The Stability of a gas bearing is treated by a new procedure in which the bearing film is characterized by its responses to step-jump displacements. Duhamel's theorem is invoked to generalize these step responses in a system of dynamical equation. Stability is determined by calculation of a "growth factor" for each degree of freedom.			

DISTRIBUTION LIST

Chief of Naval Research
Department of the Navy
Washington 25, D.C.
Attn: Code 438 (3)
Code 429
Code 463

Commanding Officer
Office of Naval Research
Branch Office
495 Summer Street
Boston, Massachusetts 02110

Commanding Officer
Office of Naval Research
Branch Office
219 S. Dearborn Street
Chicago, Illinois 60604

Commanding Officer
Office of Naval Research
Branch Office
207 West 24th Street
New York, New York 10011

Commanding Officer (25)
Office of Naval Research
London Branch Office
Box 39
Fleet Post Office
New York, New York 09510

Commanding Officer
Office of Naval Research
Branch Office
1030 East Green Street
Pasadena 1, California

Commanding Officer
Office of Naval Research
Branch Office
1000 Geary Street
San Francisco 9, California

Office of Naval Research
Resident Representative
University of Pennsylvania
3636 Walnut Street
Philadelphia, Pennsylvania 19104

Chief, Bureau of Ships
Department of the Navy
Washington 25, D.C.
Attn: Code 305 (Dr. J. H. Huth)
Code 342 (E. A. Bukzin)
Code 644C (R. M. Petros)
Code 1500 (J. A. Gorman)

Chief, Bureau of Naval Weapons
Department of the Navy
Washington 25, D.C.
Attn: Code RAPP-41 (S. M. Collegemma)
Code RREN-4 (M. R. Walter)

Director
Naval Research Laboratory
Washington, D.C.
Attn: Code 2000
Code 5230 (6)

Special Projects Office
Department of the Navy
Washington 25, D.C.
Attn: Code SP230 (D. Gold)
Code SPOOL (Dr. J. P. Craven)

Commanding Officer and Director
U.S. Navy Marine Engineering Laboratory
Annapolis, Maryland
Attn: Code 850
Code 852 (Watt V. Smith)

Material Laboratory Library
Building 291, Code 912B
New York Naval Shipyard
Brooklyn 1, New York

Superintendent
U.S. Naval Postgraduate School
Monterrey, California
Attn: Library, Technical Reports Station

Commanding Officer
U.S. Naval Avionics Facility
Indianapolis 18, Indiana
Attn: J. G. Weir

Commanding General
U.S. Army Material Command
Research & Development Directorate
Research Division
Washington, D.C. 20315
Attn: Mr. Norman L. Klein

Chief of Research and Development
Office of Chief of Staff
Department of the Army
Pentagon Building
Washington 25, D.C.

Commanding General (2)
U.S. Army Engineering R&D Laboratories
Fort Belvoir, Virginia
Attn: W. M. Crin, Nuclear Power Field Office
Technical Documents Center

DISTRIBUTION LIST (Cont.)

Aerospace Corporation
P.O. Box 95085
Los Angeles, California 90045
Attn: Library, Report Acquisitions Group

AIResearch Manufacturing Company
P.O. Box 5217
Phoenix, Arizona 85010
Attn: Mrs. J. F. Mackenzie, Librarian

American Institute of Aeronautics
and Astronautics
Technical Information Service
750 Third Avenue
New York, New York 10017

American Society of Lubrication Engineers
838 Busse Highway
Park Ridge, Illinois 60068

Chairman (2)
Research Committee on Lubrication
The American Society of Mechanical Engineers
United Engineering Center
345 East 47th Street
New York 17, New York

Dr. W. A. Gross (2)
Ampex Corporation
401 Broadway
Redwood City, California 94063

Mr. Stanley L. Zedekar
Department 244-2, Building 71
Autonetics
P.O. Box 4181
Anaheim, California 92803

C. D. Flanigen
Director of Engineering
Lycoming Division AVCO Corporation
Stratford, Connecticut

Dr. Russell Dayton
Battelle Memorial Institute
505 King Avenue
Columbus 1, Ohio

Mr. Ralph H. Larson
Research Laboratories Division
Bendix Aviation Corporation
Southfield, Michigan

Walt Tucker
Nuclear Engineering Department
Brookhaven National Laboratory
Upton, Long Island, New York

Jet Propulsion Laboratory
California Institute of Technology
4800 Oak Grove Avenue
Pasadena, California
Attn: Library

Dr. F. Osterle
Mechanical Engineering Department
Carnegie Institute of Technology
Pittsburgh, Pennsylvania 15213

Professor M. C. Shaw, Head
Department of Mechanical Engineering
Carnegie Institute of Technology
Pittsburgh, Pennsylvania 15213

Dr. W. T. Sawyer
Department of Mechanical Engineering
Catholic University
Washington, D.C.

Mr. C. W. Synder, Manager of Engineering
Defense Engineering
Defense Operations Division
Chrysler Corporation
P.O. Box 757
Detroit, Michigan 48231

Robert H. Josephson, Manager
Commercial Development
Clevite Corporation
Mechanical Research Division
540 East 105th Street
Cleveland, Ohio 44108

Professor V. Castelli
Department of Mechanical Engineering
Columbia University
New York, New York 10017

Professor H. G. Elrod, Jr. (2)
Department of Mechanical Engineering
Columbia University
New York, New York 10017

Mr. Gerald B. Speen
Division Manager
Conductron
P.O. Box 844
Northridge, California

Mr. J. W. Lower, Chief
Engineer-Inertial Components
Honeywell Aero Division
2600 Ridgway Road
Minneapolis

DISTRIBUTION LIST (Cont.)

Mr. Don Moors (2)
Litton Systems
5500 Canoga Avenue
Woodland Hills, California

Lockheed Aircraft Corporation
Missiles and Space Division
Technical Information Center
3251 Hanover Street
Palo Alto, California

Massachusetts Institute of Technology
Instrumentation Laboratory
68 Albany Street
Cambridge, Massachusetts 02139
Attn: Library, I11-109

Dr. R. W. Mann (Room 3-459A)
Engineering Projects Laboratory
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139

Professor Herbert H. Richardson
Room 3-461
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139

McDonnell Aircraft Corporation
Post Office Box 516
St. Louis, Missouri 63166
Attn: Library, Dept. 218

Dr. Beno Sternlicht
Mechanical Technology Incorporated
968 Albany-Shaker Road
Latham, New York

Mr. Carl F. Graesser, Jr.
Director of Research
New Hampshire Ball Bearings, Inc.
Peterborough, New Hampshire

Professor A. Charnes
The Technological Institute
Northwestern University
Evanston, Illinois

Mr. E. L. Swainson, Chief of Research
Precision Products Department, Nortronics
A Division of Northrop Corporation
100 Morse Street
Norwood, Massachusetts

Northrop Norair
3901 W. Broadway
Hawthorne, California 90250
Attn: Tech. Info., 3924-32

Professor P. R. Trumpler
Towne School of Civil and Mechanical
Engineering
University of Pennsylvania
Philadelphia, Pennsylvania

Radio Corporation of America
Camden 2, New Jersey
Attn: Library, Building 10-2-5

Mr. Robert S. Stiegler
Rocketdyne
Nucleonics Subdivision
6633 Canoga Avenue
Canoga Park, California

Dr. Ralph A. Burton
Southwest Research Institute
San Antonio, Texas

Mrs. Florence Turnbull
Engineering Librarian
Sperry Gyroscope Company
Great Neck, New York

W. G. Wing
Sperry Gyroscope Company
2T120
Great Neck, New York

Thomson Ramo Wooldridge
TAPCO Group
New Devices Laboratory
7209 Platt Avenue
Cleveland 4, Ohio

Union Carbide Nuclear Company
Division of Union Carbide Corporation
P.O. Box P
Oak Ridge, Tennessee 37831
Attn: R. G. Jordan

Professor J. Modrey
Department of Mechanical Engineering
Purdue University
Lafayette, Indiana

Ralph F. DeAngelias, Technical Librarian
Norden Division of United Aircraft Corp.
Helen Street
Norwalk, Connecticut 06852

Unidynamics/St. Louis Division Library
Universal Match Corporation
472 Paul Avenue
St. Louis, Missouri 63135